



LA1260

LANYARDS

Material

Steel, zinc plated, or stainless steel (300 series).

conjunction with wire lanyards. See part nos. L through LA1224. For wide range of quick release pins see part nos. QR1004 through QR5590.

Tips

For use in securing components in

Order No.	d ₁	Material	d ₂	d ₃ I/D	d ₄ O/D
LA1260.I050-C	12,70 (1/2")	Steel	1.14	11.56	13.84
LA1260.I062-C	15,87 (5/8")	Steel	1.40	11.86	17.35
LA1260.I075-C	19,05 (3/4")	Steel	1.78	17.27	20.83
LA1260.I088-C	22,22 (7/8")	Steel	1.78	20.45	24.00
LA1260.I100-C	25,4 (1")	Steel	1.78	23.62	27.18
LA1260.I125-C	31,75 (1-1/4")	Steel	2.29	29.46	34.04
LA1260.I150-C	38,10 (1-1/2")	Steel	2.67	35.43	40.77
LA1260.I200-C	50,80 (2")	Steel	3.05	47.75	53.85
LA1260.I250-C	63,50 (2-1/2")	Steel	3.94	59.56	67.44
LA1260.I300-C	76,2 (3")	Steel	3.94	72.26	80.14
LA1260.I400-C	101,6 (4")	Steel	3.94	97.66	105.54
LA1260.I050-S	12,70 (1/2")	Stainless	1.14	11.56	13.84
LA1260.I062-S	15,87 (5/8")	Stainless	1.40	11.86	17.35
LA1260.I075-S	19,05 (3/4")	Stainless	1.78	17.27	20.83
LA1260.I088-S	22,22 (7/8")	Stainless	1.78	20.45	24.00
LA1260.I100-S	25,4 (1")	Stainless	1.78	23.62	27.18
LA1260.I125-S	31,75 (1-1/4")	Stainless	2.29	29.46	34.04
LA1260.I150-S	38,10 (1-1/2")	Stainless	2.67	35.43	40.77
LA1260.I200-S	50,80 (2")	Stainless	3.05	47.75	53.85
LA1260.I250-S	63,50 (2-1/2")	Stainless	3.94	59.56	67.44
LA1260.I300-S	76,2 (3")	Stainless	3.94	72.26	80.14
LA1260.I400-S	101,6 (4")	Stainless	3.94	97.66	105.54