



SE0524

EXPANSION SEALING PLUGS

Material

Sleeve: case-hardened steel, black oxide finish.

Pin: heat-treatable steel, black oxide finish.

Technical Notes

To order please specify orifice size d_3

required (-xxx) and add to order no.

Ordering example:

Select the bore size and d_3 required (in inches).

eg. SE0524-070-030 is a 7mm pull plug restrictor with 0.030" orifice.

Important Notes

Please refer to technical pages for product installation details.

Order No.	d_1	l_1	l_2	d_2 +0.1 -0.0	l_3	d_3 inch	t
SE0524.070-XXX-C	7.0	13.0	7.5	7.0	8.0	0,012-0,13	4-40 UNC
SE0524.080-XXX-C	8.0	14.0	8.5	8.0	9.0	0,012-0,15	6-32 UNC
SE0524.090-XXX-C	9.0	16.0	9.5	9.0	10.0	0,012-0,17	8-32 UNC
SE0524.100-XXX-C	10.0	18.0	10.5	10.0	11.0	0,012-0,20	10-32 UNC
SE0524.120-XXX-C	12.0	21.0	12.5	12.0	13.0	0,012-0,24	10-32 UNC
SE0524.140-XXX-C	14.0	25.0	14.5	14.0	15.0	0,012-0,28	1/4-20 UNC
SE0524.160-XXX-C	16.0	28.0	16.5	16.0	17.0	0,012-0,30	1/4-20 UNC
SE0524.180-XXX-C	18.0	31.5	18.5	18.0	19.0	0,012-0,35	5/16-18 UNC
SE0524.200-XXX-C	20.0	35.0	20.5	20.0	21.0	0,012-0,40	3/8-16 UNC
SE0524.220-XXX-C	22.0	38.5	22.5	22.0	23.0	0,012-0,43	3/8-16 UNC